



The outlet types are:
 2 x 2-1/2" NST Hose Outlets With 1
 x 4" Monitor Flange .

27	591952-2	Stem-B	1	SS304		
26	GB/T 3452.1-2005	O-ring	2	NBR		
24	GB/T 3452.1-2005	O-ring	2	NBR		
22	GB/T 3452.1-2005	O-ring	4	NBR		
21		Bolt	2	SS304		
20	567572	Operating nut	2	Bronze, ASTM B62		
19	571002	Stem nut	2	Bronze, ASTM B62		
18	591952-3	Stem-C	1	SS304		
17	588992	Main valve holder	2	SS304		
16a	592545	Main valve	2	NBR		
16	566782	Main valve retainer	2	Bronze, ASTM B62		
15	580001	Hose nozzle	2	Bronze, ASTM B62		
14	492376	Hose nozzle gasket	2	NBR		
13	470271	Hose nozzle cap	2	Cl, ASTM A126		
12	591952-1	Stem-A	1	SS304		
11	φ72*φ48*1	Lock washer	2	SS304		
10	566881	Holder nut	2	Bronze, ASTM B62		
8	GB71-85	Screw M5x10	9	SS304		
2		Chain	2	Carbon Steel		
1	556006M	Body	1	ASTM A536 65-45-12		

No.	Drawing Number	Part Name	QTY	Material

WEFLO Valve Co., Ltd.
 WET BARREL FIRE HYDANT
 2-HOSE ASSEMBLY
 WITH MONITOR FLANGE

C503-2H0PM