



Dimensions						
Size	4"	5"	6"	8"	10"	12"
L	9"	10"	10-1/2"	11-1/2"	13"	14"
H	13-3/4"	16-1/8"	17-15/16"	21-7/16"	25-3/8"	28-3/4"
D	12"	12"	12"	12"	12"	12"

Notes:

1. Pressure rating: 300PSI
2. UL Listed and FM Approved
3. Certified to NSF/ANSI 61 & 372

No.	Description	Material Specifications
1	Body	Ductile Iron, ASTM A536 65-45-12
2	Wedge	Ductile Iron, EPDM Encapsulated
3	Wedge Nut	ASTM C67400
4	Stem	Stainless Steel, AISI 304
5	Gasket	EPDM
6	Bonnet	Ductile Iron, ASTM A536 65-45-12
7	O-ring	EPDM
8	Thrust Ring	ASTM C67400
9	O-ring	EPDM
10	Post Flange	Carbon Steel
11	Operating Nut	Ductile Iron, ASTM A536 65-45-12
12	Washer	Stainless Steel, AISI 304
13	Bolts	Stainless Steel, AISI 304
14	Cap	Plastic
15	Dustproof Ring	EPDM
16	Bolts	Stainless Steel, AISI 304
17	Washer	Carbon Steel, Zinc Plated
18	Gland	Ductile Iron, ASTM A536 65-45-12
19	O-ring	EPDM
20	Bolts	Stainless Steel, AISI 304



Post Indicator Gate Valve 4" to 12", Flanged Ends

F0211-300



WEFLO VALVE LLC

E-mail: info@weflovalve.com

Website: www.weflo.com / www.weflovalve.com