



The outlet types are:
 1 x 2-1/2" NST Hose Outlets + 1 x 4" (or 4.5") NST
 pumper connection
 (or 5" nonthreaded storz)

26	GB/T 3452.1-2005	O-ring	1	NBR	
25	GB/T 3452.1-2005	O-ring	1	NBR	
24	GB/T 3452.1-2005	O-ring	2	NBR	
23	571001	Stem nut	1	Bronze, ASTM B62	
22	GB/T 3452.1-2005	O-ring	4	NBR	
21		Bolt	2	SS304	
20	567572	Operating nut	2	Bronze, ASTM B62	
19	571002	Stem nut	1	Bronze, ASTM B62	
18	591952-3	Stem-C	1	SS304	
17	588992	Main valve holder	1	SS304	
16a	592545	Main valve	1	NBR	
16	566782	Main valve retainer	1	Bronze, ASTM B62	
15	580001	Hose nozzle	1	Bronze, ASTM B62	
14	492376	Hose nozzle gasket	1	NBR	
13	470271	Hose nozzle cap	1	Cl ASTM A126	
12	591952-1	Stem-B	1	SS304	
11	$\phi 72 \times \phi 48 \times 1$	Lock washer	2	SS304	
10	566881	Holder nut	2	Bronze, ASTM B62	
9	588991	Main valve holder	1	SS304	
8	GB71-85	Screw M5x10	9	SS304	
7	566781	Main valve retainer	1	Bronze, ASTM B62	
6	592544	Main valve	1	NBR	
5	492410	Pumper nozzle gasket	1	NBR	
4	481008	Pumper Nozzle	1	Bronze, ASTM B62	
3	473694	Nozzle cap	1	Cast Iron	
2		Chain	3	Carbon Steel	
1	556005	Body	1	ASTM A536 65-45-12	
No.	Drawing Number	Part Name	QTY	Material	

WEFLO Valve Co., Ltd.

WET BARREL FIRE HYDANT
 WITH 1-HOSE&1-PUMPER
 ASSEMBLY

C503-1H1P