



Dimensions							
Size	3"	4"	5"	6"	8"	10"	12"
L	8"	9"	10"	10-1/2"	11-1/2"	13"	14"
H	11-7/8"	12-7/8"	15-7/16"	17-3/16"	20-15/16"	24-7/8"	28-5/16"
D	10"	10"	12"	12"	14"	16"	16"

Notes:

1. Pressure rating: 300PSI
2. UL Listed and FM Approved



No.	Description	Material Specifications
1	Body	Ductile Iron, ASTM A536 65-45-12
2	Wedge	Ductile Iron, EPDM Encapsulated
3	Wedge Nut	ASTM C67400
4	Stem	Stainless Steel, AISI 420
5	Gasket	EPDM
6	Bonnet	Ductile Iron, ASTM A536 65-45-12
7	O-ring	EPDM
8	Thrust Ring	ASTM C67400
9	O-ring	EPDM
10	Gland	Ductile Iron, ASTM A536 65-45-12
11	O-ring	EPDM
12	Dustproof Ring	EPDM
13	Bolts	Carbon Steel Gr8.8
14	Handwheel	Ductile Iron, ASTM A536 65-45-12
15	Plug (Optional)	Malleable Iron

NRS Gate Valve 3" to 12" with Handwheel, Flanged Ends

F0211-300



**WEFLO VALVE LLC**

E-mail: [info@weflovalve.com](mailto:info@weflovalve.com)

Website: [www.weflo.com](http://www.weflo.com) / [www.weflovalve.com](http://www.weflovalve.com)