



Dimensions							
Size	3"	4"	5"	6"	8"	10"	12"
L	8"	9"	10"	10-1/2"	11-1/2"	13"	14"
H	11-5/8"	13-3/4"	16-1/8"	17-15-16"	21-7/16"	25-3/8"	28-3/4"

Notes:

1. Pressure rating: 300PSI
2. UL Listed and FM Approved



No.	Description	Material Specifications
1	Body	Ductile Iron, ASTM A536 65-45-12
2	Wedge	Ductile Iron, EPDM Encapsulated
3	Wedge Nut	ASTM C67400
4	Stem	Stainless Steel, AISI 420
5	O-ring	EPDM
6	Bonnet	Ductile Iron, ASTM A536 65-45-12
7	O-ring	EPDM
8	Packing	Graphite
9	O-ring	EPDM
10	Thrust Collar	ASTM C67400
11	O-ring	EPDM
12	O-ring	EPDM
13	Bolts	Stainless Steel AISI 304
14	Nut Cap	Ductile Iron, ASTM A536 65-45-12
15	Plug (Optional)	Malleable Iron

NRS Gate Valve 3" to 12", Flanged Ends

F0211-300



WEFLO VALVE LLC

E-mail: info@weflovalve.com

Website: www.weflo.com / www.weflovalve.com