



Size	L	H
14"	16.5"	32.87"
16"	16.5"	35.83"
18"	17"	41.34"
20"	18"	44.09"
24"	20"	50.79"

Notes:  
 Pressure rating 250PSI for valve 14"-18",  
 200PSI for valve 20"-24".



No.	Description	Material Specifications
1	Body	Ductile Iron, ASTM A536 65-45-12
2	Wedge	Ductile Iron, EPDM Encapsulated
3	Wedge Nut	ASTM C67400
4	Stem	Stainless Steel, AISI 431
5	Gasket	EPDM
6	Bolts	Carbon Steel, ASTM A307B
7	Nuts	Carbon Steel, ASTM A307B
8	Washers	Carbon Steel, Zinc Plated
9	Bonnet	Ductile Iron, ASTM A536 65-45-12
10	O-Ring	EPDM
11	Thrust Collar	ASTM C67400
12	O-Ring	EPDM
13	Gland	Ductile Iron, ASTM A536 65-45-12
14	O-Ring	EPDM
15	Dustproof Ring	NBR
16	Operating Nut	Ductile Iron, ASTM A536 65-45-12
17	Nut Cap	Plastic
18	Bolt	Carbon Steel, Zinc Plated
19	Bolts	Carbon Steel, ASTM A307B
20	Eyebolts	Carbon Steel, ASTM A307B
21	Washers	Carbon Steel, Zinc Plated

NRS GATE VALVE 14"-24" WITH OPERATING NUT

F0233-200&250



**WEFLO VALVE LLC**

E-mail: [info@weflovalve.com](mailto:info@weflovalve.com)

Website: [www.weflo.com](http://www.weflo.com) / [www.weflovalve.com](http://www.weflovalve.com)