


Size	2"	2.5"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"	20"	24"
L	8"	8.5"	9.5"	11.5"	13"	14"	19.5"	24.5"	27.5"	31"	36"	36"	40"	48"
H	4.92"	5.39"	5.79"	6.54"	7.48"	8.54"	10.43"	11.81"	13.46"	15.83"	18.58"	19.69"	20.24"	25.59"

A-A Section



NOTES:

1. In accordance with AWWA C508 Standard.
2. ANSI B16.1, Class 125 Flange Drilling.
3. 200 psi rated water working pressure.
4. Suitable for mounting in horizontal or vertical Position (with vertical flow upwards)
5. Outside lever and adjustable weight or lever and spring

No.	Part Name	Material
1	Body	ASTM A536 65-45-12
2	Disc	ASTM A536 65-45-12
3	Washer	Carbon Steel
4	Bolt	SS304
5	Nut	SS304
6	Pin	SS304
7	Gasket	Graphite
8	Bonnet	ASTM A536 65-45-12
9	Bolt	Carbon Steel
10	Nut	Carbon Steel
11	Seat	ASTM B62
12	Disc Ring	Rubber EPDM
13	Nut	ASTM B16
14	Washer	PTFE
15	Hanger	ASTM A536 65-45-12
16	Stem	AISI 304
17	Bushing	ASTM B16
18	O-ring	EPDM
19	Nut	Carbon Steel
20	Lever	Carbon Steel
21	Bolt	Carbon Steel
22	Weight	ASTM A126 Class B

AWWA C508 SWING CHECK VALVE WITH LEVER AND WEIGHT

FIG.5110



WEFLO VALVE LLC

E-mail: info@weflovalve.com

Website: www.weflo.com / www.weflovalve.com