

Shotgun Riser Check Valve, Grooved Ends

FIG. F3322
FIG.F3322B

Specifications

- Meet or exceed the requirements of UL 312 and FM 1210 Standard.
- Spring Loaded for Fast Closure.
- It is used in wet pipe fire protection systems, as well as the pre-action systems where not need a mechanical alarm.
- Drain plug at the bottom under the inlet end for attaching a drain valve.
- Excellent Flow Characteristics.
- Superior design featuring exceptionally low pressure losses at high flow rates.
- Rubber Disc Facing and Bronze Seat Ring.
- Grooved Connections are cut in accordance with AWWA C606 or other standard Groove Specifications for Steel Pipe.
- F3322 with or without Trim.
- Rated Working Pressure
300 psi for valve with Trim
350 psi for valve without Trim
- UL 312 / ULC Listed and FM 1210 Approved.

Schematic




FIG. F3322


FIG. F3322B

Corrosion Protection

- Fusion Bonded Epoxy Coated Interior and Exterior to AWWA C550 Standard.

Material Specifications

Part	Material	ASTM Specification
Body	Ductile Iron	A536 Grade 65-45-12
Body Seat Ring	Bronze	B62 C83600
Disc	Stainless Steel	A351 Grade CF8
Disc Facing	Rubber	D2000 EPDM
Spring	Stainless Steel	A276 Type 304
Hinge Pin	Stainless Steel	A276 Type 304
Disc Facing Bolt/Nut	Stainless Steel	A276 Type 304
Angle Drain Valve	Bronze	B148 C95500
3-Way Valves	Bronze	B148 C95500
Nipples	Stainless Steel	A276 Type 304
Air/Water Gauges	Assembly	



Main Dimensions (mm/inch)

Size	1.25	1.5	2	2.5	3	4	6	8
L	160/6.3	160/6.3	170/6.7	183/7.2	198/7.8	218/8.6	270/10.62	325/12.8
H	65/2.5	65/2.5	75/3	80/3.13	90/3.5	102/4	127/5	160/6.3

Notes

- Designs, materials and specifications shown are subject to change without notice due to the continuous development of our products.